

Rodamiento de agujas 22BTM2812-JTEKT - 22BTM2812-JTEKT

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/22btm2812-jtekt>

Drawn cup needle roller bearings



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾	
F _w	D	C	b min.	C ₀	C _{0r}	Oil lub.	Caged type	
							With open ends	With closed end
22	28	12	9.3	9.10	13.5	16 000	22BTM2812	

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φG) min.	max.	Housing bore dia. (φT) min.	max.	With open ends	With closed end
—	—	21.987	22.000	27.972	27.993	14	16

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952471075
Diámetro interior	22 mm
Diámetro exterior	28 mm
Espesor	12 mm
Peso	14 g
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE