

Rodamiento de agujas BTM2225-JTEKT - BTM2225-JTEKT

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/btm2225-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾	
F _w	D	C	b min.	C _r	C _{0r}	Oil lub.	Caged type	
							With open ends	With closed end
22	29	25	—	20.4	36.1	16 000	BTM2225	

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (d6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	21.987	22.000	28.972	28.993	37	—

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952471235
Diámetro interior	22 mm
Diámetro exterior	29 mm
Espesor	25 mm
Peso	37 g
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE