

## Rodamiento de agujas BTM2428-JTEKT - BTM2428-JTEKT

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/btm2428-jtekt>

Drawn cup needle roller bearings **Koyo**



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>	
$F_w$	$D$	$C$	$b$ min.	$C_0$	$C_{0e}$	Oil lub.	Caged type	
							With open ends	With closed end
24	31	28	—	23.9	43.0	15 000	<b>BTM2428</b>	

  

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (H6) min.	max.	Housing bore dia. (H7) min.	max.	With open ends	With closed end
—	—	23.987	24.000	30.967	30.992	44	—

### CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952471297
Diámetro interior	24 mm
Diámetro exterior	31 mm
Espesor	28 mm
Peso	44 g
Envasado	1
Estándar	Ninguna norma

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE