


Rodamiento de agujas BM2516-JTEKT - BM2516-JTEKT

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/bm2516-jtekt>

Drawn cup needle roller bearings 

Full complement type
With open ends



BM, BHM

| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ | |
|--------------------------|-----|----------|-------------------------|----------|--------------------------------------|-------|---------------------------|-----------------|
| F_w | D | C | C_r | C_{0r} | Oil lub. | | Caged type | |
| | | b min. | | | | | With open ends | With closed end |
| 25 | 32 | 16 | — | 18.7 | 37.9 | 5 100 | | |

| Full complement type | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------------------|-----------------------------|----------------------|-----------------------------|-------------------|-----------------|
| | With open ends | | With closed end | | With open ends | With closed end |
| BM2516 | Shaft dia. (F6) min. | Housing bore dia. (N7) max. | Shaft dia. (F6) max. | Housing bore dia. (N7) min. | 28 | — |
| | 24.987 | 25.000 | 31.967 | 31.992 | | |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| N° Ean13 | 4549250003523 |
| Diámetro interior | 25 mm |
| Diámetro exterior | 32 mm |
| Espesor | 16 mm |
| Peso | 28 g |
| Envasado | 1 |

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE