

Rodamiento de agujas BHTM2520-1-JTEKT - BHTM2520-1-JTEKT

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/bhtm2520-1-jtekt>

Drawn cup needle roller bearings



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ |
|--------------------------|-----|-----|----------|-------------------------|----------|--------------------------------------|---|
| F_w | D | C | b min. | C_r | C_{0r} | Oil lub. | Caged type With open ends With closed end |
| 25 | 33 | 20 | 17.3 | 19.2 | 29.7 | 14 000 | BHTM2520-1 |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|-----------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (f6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| — | — | 24.987 | 25.000 | 32.967 | 32.992 | 37 | 41 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| N° Ean13 | 4549250003165 |
| Diámetro interior | 25 mm |
| Diámetro exterior | 33 mm |
| Espesor | 20 mm |
| Peso | 37 g |
| Envasado | 1 |

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE