

Rodamiento de agujas BTM424709AJ-JTEKT - BTM424709AJ-JTEKT

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/btm424709aj-jtekt>

Drawn cup needle roller bearings 



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ | |
|--------------------------|-------|------|-------------------------|----------------|--------------------------------------|----------|---------------------------|-----------------|
| F _w | D | C | b min. | C ₀ | C _{0r} | Oil lub. | Caged type | |
| | | | | | | | With open ends | With closed end |
| 41.50 | 46.50 | 8.50 | — | 7.00 | 13.9 | 9 200 | BTM424709AJ | |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|-----------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (d6) min. | max. | Housing bore dia. (D7) min. | max. | With open ends | With closed end |
| — | — | 41.484 | 41.500 | 46.467 | 46.492 | 15 | — |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| N° Ean13 | 3663952472690 |
| Diámetro interior | 41.5 mm |
| Diámetro exterior | 46.5 mm |
| Espesor | 8.5 mm |
| Peso | 15 g |
| Envasado | 1 |

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE