


## Rodamiento de agujas BTM5015-JTEKT - BTM5015-JTEKT

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/agujas/btm5015-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_0$	$C_{0r}$	Oil lub.	Caged type With open ends With closed end
50	62	15	—	24.3	36.4	7 300	<b>BTM5015</b>

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (H6) min.	max.	Housing bore dia. (H7) min.	max.	With open ends	With closed end
—	—	49.984	50.000	61.961	61.991	73	—

### CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952472935
Diámetro interior	50 mm
Diámetro exterior	62 mm
Espesor	15 mm
Peso	73 g
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE