


Rodamiento rodillos NN3060K-JTEKT - NN3060K-JTEKT

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/rodillos/nn3060k-jtekt>

Double-row cylindrical roller bearings **Koyo**



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min ⁻¹)		Bearing No.	
d	D	B	r min.	F _w	C	C ₀₇	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
300	460	118	4	—	418	1 290	2 460	1 100	1 300	NN3060K

Mounting dimensions (mm)		Cylindrical bore		Tapered bore		Mass (kg)	
d _a min.	d _a max.	D _a min.	D _a max.	r _a min.	r _a max.	Cylindrical bore	Tapered bore
316	—	—	444	421	3	70.8	68.7

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952474014
Diámetro interior	300 mm
Diámetro exterior	460 mm
Espesor	118 mm
Peso	68700 g
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE