


## Rodamiento rodillos NN3060K-JTEKT - NN3060K-JTEKT

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/rodillos/nn3060k-jtekt>

Double-row cylindrical roller bearings **Koyo**



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )		Bearing No.		
<i>d</i>	<i>D</i>	<i>B</i>	<i>r</i> min.	<i>F<sub>w</sub></i>	<i>E<sub>a</sub></i>	<i>C</i>	<i>C<sub>07</sub></i>	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
300	460	118	4	—	418	1 290	2 460	1 100	1 300		<b>NN3060K</b>

		Mounting dimensions (mm)						(Refer.) Mass (kg)	
Cylindrical bore	Tapered bore	<i>d<sub>a</sub></i>		<i>D<sub>a</sub></i>		<i>r<sub>a</sub></i>		Cylindrical bore	Tapered bore
		min.	max.	min.	max.	min.	max.		
		316	—	—	444	421	3	70.8	68.7

### CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952474014
Diámetro interior	300 mm
Diámetro exterior	460 mm
Espesor	118 mm
Peso	68700 g
Envasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE