


Rodamiento rodillos NQI22-16-JTEKT - NQI22-16-JTEKT

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/rodillos/nqi22-16-jtekt>

Machined ring needle roller bearings  **Koyo**
F_W 29 ~ 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No. Without inner ring	
F _w	d	D	B	C _r	C _{0r}	Oil lub.			
26	22	34	16	14.1	24.2	18 000	—	—	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				d ₂	D ₂	r ₂	Without inner ring	With inner ring	
NQI22/16				24	32	0.3	0.037	0.056	—

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952482477
Diámetro interior	22 mm
Diámetro exterior	34 mm
Espesor	16 mm
Peso	56 g
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE