


Rodamiento rodillos 25NQI4425A-JTEKT - 25NQI4425A-JTEKT

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/rodillos/25nqi4425a-jtekt>

Machined ring needle roller bearings  **Koyo**
F_W 29 ~ 37 mm
With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No. Without inner ring	
F _w	d	D	B	C _r	C _{0r}	Oil lub.	Without inner ring		
30	25	44	25	25.5	36.0	48.8	14 000	—	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring				
25NQI4425A				27	42	0.3	—	0.161	—

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952482767
Diámetro interior	25 mm
Diámetro exterior	44 mm
Espesor	25 mm
Peso	161 g
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE