

Rodamiento rodillos NQ40-20-JTEKT - NQ40-20-JTEKT

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/rodillos/nq40-20-jtekt>

Machined ring needle roller bearings 
F_w 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C _{0r}	Oil lub.		Without inner ring	
40	35	50	20	—	0.3	27.2	48.8	12 000	NQ40/20
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring				
	d ₁	D ₁	r ₁	Without inner ring	With inner ring				
	max.	max.	max.	0.085	0.129				

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952483030
Diámetro interior	40 mm
Diámetro exterior	50 mm
Espesor	20 mm
Peso	85 g
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE