

Rodamiento rodillos RNA49-48R-JTEKT - RNA49-48R-JTEKT

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/rodillos/rna49-48r-jtekt>

Machined ring needle roller bearings  **Koyo**
F_W 29 ~ 37 mm

Without inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. Without inner ring |
|--------------------------|---|----|----|-------------------------|-----------------|------------------------------------|--|-----------------|-----------------------------------|
| F _w | d | D | B | C _r | C ₁₀ | Oil lub. | | | |
| 55 | — | 70 | 22 | — | 46.9 | 76.5 | 8 300 | RNA49/48R | |
| Mounting dimensions (mm) | | | | (Note 1) Mass (kg) | | (Note 1) Applicable inner ring No. | | | |
| With inner ring | | | | d ₁ | D ₁ | r _a | Without inner ring | With inner ring | |
| | | | | min. | max. | max. | — | — | |
| | | | | — | 66 | 0.6 | 0.174 | — | |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| N° Ean13 | 3663952483481 |
| Diámetro interior | 55 mm |
| Diámetro exterior | 70 mm |
| Espesor | 22 mm |
| Peso | 174 g |
| Envasado | 1 |

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE