


Rodamiento rodillos RNA49-48R-JTEKT - RNA49-48R-JTEKT

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/rodillos/rna49-48r-jtekt>

Machined ring needle roller bearings ————— **Koyo**
F_W 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds ¹⁾ (min ⁻¹)		Bearing No. Without inner ring
F _w	d	D	B	C _r	C ₁₀	Oil lub.			
55	—	70	22	46.9	76.5	8 300		RNA49/48R	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				d _s	D _s	r _s	Without inner ring	With inner ring	
				max.	max.	max.			
				—	66	0.6	0.174	—	

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952483481
Diámetro interior	55 mm
Diámetro exterior	70 mm
Espesor	22 mm
Peso	174 g
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE