

Rodamiento rodillos NA5916-JTEKT - NA5916-JTEKT

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/rodillos/na5916-jtekt>

Machined ring needle roller bearings 
F_w 29 ~ 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No. Without inner ring	
F _w	d	D	B	C _r	C _{10r}	Oil lub.			
90	80	110	40	114.0	232.0		5 100	—	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				d ₁ min.	D ₁ max.	r ₁ max.	Without inner ring	With inner ring	
NA5916				85	105	1	0.681	1.39	IRM809040

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952483993
Diámetro interior	80 mm
Diámetro exterior	110 mm
Espesor	40 mm
Peso	1090 g
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE