


Rodamiento rodillos NA5920-JTEKT - NA5920-JTEKT

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/rodillos/na5920-jtekt>

Machined ring needle roller bearings 
F_w 29 ~ 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No. Without inner ring	
F _w	d	D	B	C _r	C ₁₀	Oil lub.	Without inner ring		
115	100	140	54	189.0	418.0	4 000	—		
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring	With inner ring			
NA5920				106.5	133.5	1	1.49	2.53	IRM10011554

[Note] 1) Limiting speeds of bearing number NA49...LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952484242
Diámetro interior	100 mm
Diámetro exterior	140 mm
Espesor	54 mm
Peso	2530 g
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE