


Rodamiento conico 2560X-2526X-TIMKEN - 2560X-2526X-TIMKEN

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/2560x-2526x-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic ⁽¹⁾ C ₁	Factor ⁽²⁾ e	Dynamic ⁽¹⁾ C ₂	Factor ⁽²⁾ e ₂	Static C ₃	Inner	Outer	
mm	mm	mm	N		N	N	N			
25.257	72.000	25.812	82700	0.27	21700	10200	214	9400	2560X	
0.9953	2.8346	0.9275	1850		480	226		2280	2526X	

Bearing Dimensions										Geometry Factors			Bearing Weight	
Width B	Width C	ER. Dr. α ⁽¹⁾	Max Shaft Fillet Radius R _{f1}	Backing Shoulder Dia. d _s	Max Housing Fillet Radius r _h	Backing Shoulder Dia. D _s	Cage A ₁ ⁽²⁾	A ₂ ⁽²⁾	G ₁	G ₂	C ₃			
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg	
25.257	19.250	-8.8	2.8	38.0	33.5	2.8	65.0	61.8	8.8	8.8	23.6	9.8	0.0658	6.50
0.9953	0.7500	-0.34	0.09	1.42	1.56	0.09	2.56	2.40	0.03	0.04				1.11

CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
N° Ean13	3663952136462
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE