


Casquillos de agujas BAM1312-IKO - BAM1312-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/bam1312-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g	
	Standard	Mass (Ref.) g	Closed end											
20.638 ($\frac{3}{8}$)	--	--	--	--	--	--	--	--	--	BAM 1312	23.5	--	--	
Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾		Assembled inner ring	
F_w	D	C	Shaft dia. ϕ Max.	Housing bore dia. $J7$ Max.	Shaft dia. ϕ Min.	Housing bore dia. $J7$ Min.	C	C_0	C_0	N	N	rpm	IRB 912	
20.638 $\frac{3}{8}$	26.988 $1 \frac{1}{8}$	19.051 $\frac{3}{4}$	20.638	20.625	27.000	26.979	12 400	19 000	19 000	19 000				

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952173078
Diámetro interior	20.64 mm
Diámetro exterior	26.99 mm
Espesor	19.05 mm
Invasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE