

Casquillos de agujas
BAM1516-IKO - BAM1516-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/bam1516-iko>



SHELL TYPE NEEDLE ROLLER BEARINGS

Inch Series

BAM BHAM

Shaft dia.		Identification number							
mm (inch)	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g
23.812 (9/16)	—	—	—	—	—	BAM 1516	35.5	—	—

Boundary dimensions mm (inch)			Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F _w	D	C	Shaft dia. h8	Housing bore dia. J7	Max. Min.	N	N	rpm	
23.812 1/32	30.162 1/8	25.40 (1.000) 2.8	23.812	23.799	30.176 30.151	18 900	34 300	16 000	IRB 1116

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.

Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952173214
Diámetro interior	23.81 mm
Diámetro exterior	30.16 mm
Espesor	25.4 mm
Envasado	1

contacto@123rodamiento.mx
+34 911 436 830
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE