


Casquillos de agujas BAM812-IKO - BAM812-IKO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/bam812-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
12.700 (1/2)	—	—	—	—	—	—	BAM 812	11.3	—		
Boundary dimensions mm(inch)		Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾	Assembled inner ring		
<i>F_w</i>	<i>D</i>	<i>C</i>	<i>h₈</i> Max.	<i>J₇</i> Max.	Min.	Max.	Min.	N	N	rpm	
12.700 (1/2)	17.462 (2/3)	19.05 (7/8)	12.700	12.689	17.472	17.454		7 840	11 000	30 000	IRB 58

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952173573
Diámetro interior	12.7 mm
Diámetro exterior	17.46 mm
Espesor	19.05 mm
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE