

Rodamiento conico 938-932-JTEKT - 938-932-KOYO

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/938-932-koyo>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)								Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _a max.	<i>r</i> _b max.	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.	
114.300	212.725	66.675	66.675	53.975	7.1	3.2	450	674	1 800	2 400	

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
938	932	47.6	141.0	128.0	187.0	193.0	7.1	3.2	0.33	1.84	1.01	5.96	4.07

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	4549250209734
Diámetro interior	114.3 mm
Diámetro exterior	212.72 mm
Espesor	53.9 mm
2º Espesor	66.6 mm
Envasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE