

Rodamiento conico 15100S-15250X-TIMKEN - 15100S-15250X-TIMKEN

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/15100s-15250x-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic ⁽¹⁾ C ₁	Factor ⁽²⁾ e	Dynamic ⁽¹⁾ C ₂	Factor ⁽²⁾ e ₂	Static C ₃	Inner	Outer	
mm	mm	mm	N		N	N	N			
25.400	63.500	20.638	12900	1.21	12500	8216	1.67	12000	15100-S	
1.0000	2.5000	0.8125	13500		14900	3096		12100	15250X	

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft		Housing		Cage					G ₁	G ₂	C ₃			
Width B	Width C	ER. Dr. r ⁽¹⁾	Max Shaft Fillet Radius R ⁽¹⁾	Backing Shoulder Dia. d ₁	Max Housing Fillet Radius r ⁽²⁾	Backing Shoulder Dia. D ₁	A ₁ ⁽³⁾	A ₂ ⁽³⁾						
20.638	15.875	-5.8	1.3	31.5	33.5	1.5	59.0	59.0	1.2	1.1	14.6	10.0	0.9008	0.23
0.8125	0.6250	-0.23	0.05	1.24	1.32	0.06	2.32	2.17	0.04	0.05				0.72

CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
N° Ean13	3663952309507
Diámetro interior	25.4 mm
Diámetro exterior	63.5 mm
Espesor	20.64 mm
Peso	325 g
Envasado	1
Estándar	Ninguna norma

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE