


Rodamiento conico

HM88630-HM88610A-TIMKEN - HM88630-HM88610A-TIMKEN

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/hm88630-hm88610a-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



| Bearing Dimensions | | | Load Ratings | | | | | Part Number | |
|--------------------|--------|---------|---------------------------------------|-------------------------|---------------------------------------|---------------------------------------|-----------------------|-------------|----------|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ e | Dynamic ⁽¹⁾ C ₂ | Factor ⁽²⁾ C _{2e} | Static C ₃ | Inner | Outer |
| mm | mm | mm | N | | N | N | N | | |
| 25.400 | 72.232 | 25.400 | 79000 | 0.30 | 13900 | 19000 | 1.07 | HM88630 | HM88610A |
| 1.0000 | 2.8450 | 1.0000 | 17500 | | 4600 | 4100 | | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight |
|--------------------|---------|--------------------------|--|--------------------------------------|--|--------------------------------------|-------------------------------|-------------------------------|----------------|------------------|----------------|--------|----------------|
| Shaft | | Housing | | Cage | | | | | G ₁ | G ₂ | C ₃ | | |
| Width B | Width C | ER. Dr. r ⁽¹⁾ | Max Shaft Fillet Radius R ⁽¹⁾ | Backing Shoulder Dia. d ₁ | Max Housing Fillet Radius r ⁽¹⁾ | Backing Shoulder Dia. D ₁ | A ₁ ⁽¹⁾ | A ₂ ⁽¹⁾ | | | | mm | mm |
| 25.400 | 19.842 | -4.6 | 0.8 | 35.5 | 0.8 | 69.0 | 61.8 | 1.6 | 1.7 | 25.4 | 5.4 | 0.9022 | 6.58 |
| 1.0000 | 0.7812 | -0.18 | 0.03 | 1.56 | 0.03 | 2.72 | 2.40 | 0.06 | 0.07 | | | | 1.29 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | TIMKEN |
| N° Ean13 | 3663952309569 |
| Diámetro interior | 25.4 mm |
| Diámetro exterior | 72.23 mm |
| Espesor | 25.4 mm |
| Invasado | 1 |

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE