


Rodamiento conico 4C-6-TIMKEN - 4C-6-TIMKEN

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/4c-6-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic ⁽¹⁾ C ₁	Factor ⁽²⁾ e	Dynamic ⁽¹⁾ C _{2e}	Factor ⁽²⁾ K	Static C ₂	Inner	Outer	
mm	mm	mm	N		N		N			
17.462	44.456	12.700	20500	0.67	13900	1.22	29000	4C	6	
0.6875	1.7500	0.5000	4550		1190		6540			

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					G ₁	G ₂	C ₃		
Width B	Width C	ER Co. μm	Max Shaft Fillet Radius R _f	Backing Shoulder Dia. d _s	Max Housing Fillet Radius r ₁	Backing Shoulder Dia. D _s	Cage A ₁ ⁽¹⁾	A ₂ ⁽¹⁾	A ₁ ⁽¹⁾					
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm					
11.988	9.525	-1.8	1.5	22.8	24.5	1.5	41.8	38.0	0.8	1.6	4.6	2.6	0.0406	0.09
0.4680	0.3750	-0.07	0.06	0.87	0.96	0.06	1.61	1.50	0.03	0.07				0.21

CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
N° Ean13	3663952309637
Diámetro interior	17.46 mm
Diámetro exterior	44.45 mm
Espesor	12.7 mm
Invasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE