


Rodamiento conico 24112-24261-TIMKEN - 24112-24261-TIMKEN

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/24112-24261-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic ^{1/3} C ₁	Factor ^{1/3} e	Dynamic ^{1/3} C ₂	Factor ^{1/3} C _{2e}	Static C ₀	Inner	Outer	
mm	mm	mm	N		N	N	N			
28.575	66.421	19.050	9200	0.34	14500	8400	1.72	52000	24112	24261
1.1250	2.6150	0.7500	13500		3300	1000		12400		

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft		Housing		Cage					G ₁	G ₂	C ₃			
Width B	Width C	ER. Dr. a ^{1/2}	Max Shaft Fillet Radius R ₁	Backing Shoulder Dia. d ₁	Max Housing Fillet Radius r ^{1/2}	Backing Shoulder Dia. D ₁	A ₁ ^{1/2}	A ₂ ^{1/2}						
19.054	15.875	-4.8	1.5	36.0	36.0	1.5	61.0	58.0	8.3	1.5	14.0	0.2	0.0500	0.21
0.7470	0.6250	-0.19	0.06	1.34	1.42	0.06	2.40	2.28	0.01	0.06				0.09

CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
N° Ean13	3663952309828
Diámetro interior	28.58 mm
Diámetro exterior	66.42 mm
Espesor	19.05 mm
Invasado	1

contacto@123rodamiento.mx

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE