


## Rodamiento conico 2558-2530-TIMKEN - 2558-2530-TIMKEN

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/2558-2530-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factor <sup>(2)</sup> e <sub>2</sub>	Static C <sub>3</sub>	Inner	Outer	
mm	mm	mm	N		N	N	N			
30.162	66.421	25.400	82700	0.27	21700	10200	2.14	94400	2558	2530
1.1875	2.6150	1.0000	18500		4800	2200		21200		

Bearing Dimensions										Geometry Factors			Bearing Weight	
Width		ER. Dr.		Max Shaft		Backing		Max Housing		Backing		Cage		
B	C	mm	μm	Fiber Radius	Shoulder Dia.	Shoulder Dia.	Shoulder Dia.	Fiber Radius	Shoulder Dia.	Shoulder Dia.	Shoulder Dia.	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	
25.207	28.638	-0.6	2.3	36.5	48.8	0.8	62.5	59.8	0.8	0.8	23.6	9.6	0.0608	0.43
0.9963	0.9125	-0.34	0.09	1.44	1.97	0.03	2.46	2.38	0.03	0.04				0.94

### CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
N° Ean13	3663952310008
Diámetro interior	30.16 mm
Diámetro exterior	66.42 mm
Espesor	25.4 mm
Invasado	1

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE