


## Rodamiento conico 3483-3420-TIMKEN - 3483-3420-TIMKEN

<https://www.123rodamiento.mx/rodamiento-cojinete/rodamiento-rodillos/conico/3483-3420-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



| Bearing Dimensions |        |         | Load Ratings                         |                        |                                      |                        |                       |       |       | Part Number |  |
|--------------------|--------|---------|--------------------------------------|------------------------|--------------------------------------|------------------------|-----------------------|-------|-------|-------------|--|
| Bore d             | O.D. D | Width T | Dynamic <sup>1)</sup> C <sub>1</sub> | Factor <sup>2)</sup> e | Dynamic <sup>3)</sup> C <sub>2</sub> | Factor <sup>4)</sup> K | Static C <sub>3</sub> | Inner | Outer |             |  |
| mm                 | mm     | mm      | N                                    |                        | N                                    |                        | N                     |       |       |             |  |
| 33.337             | 79.375 | 29.378  | 105000                               | 0.37                   | 27100                                | 1.60                   | 119000                | 3420  | 3420  |             |  |
| 1.3125             | 3.1250 | 1.1563  | 23500                                |                        | 6190                                 |                        | 26800                 |       |       |             |  |

| Bearing Dimensions |         |                         |   |                                      |                                      |   |                                      |                                      |                                   | Geometry Factors                  |                |                | Bearing Weight |                |
|--------------------|---------|-------------------------|---|--------------------------------------|--------------------------------------|---|--------------------------------------|--------------------------------------|-----------------------------------|-----------------------------------|----------------|----------------|----------------|----------------|
| Width B            | Width C | ER. Dr. a <sup>1)</sup> | Max Shaft Fillet Radius R <sup>2)</sup> | Backing Shoulder Dia. d <sub>1</sub> | Backing Shoulder Dia. d <sub>2</sub> | Max Housing Fillet Radius r <sup>3)</sup> | Backing Shoulder Dia. D <sub>1</sub> | Backing Shoulder Dia. D <sub>2</sub> | Cage A <sub>1</sub> <sup>4)</sup> | Cage A <sub>2</sub> <sup>5)</sup> | G <sub>1</sub> | G <sub>2</sub> |                | C <sub>1</sub> |
| mm                 | mm      | mm                      | mm                                      | mm                                   | mm                                   | mm  | mm                                   | mm                                   | mm                                | mm                                |                |                |                | kg             |
| 29.771             | 29.812  | -0.6                    | 0.8                                     | 42.5                                 | 43.8                                 | 3.3                                       | 74.9                                 | 67.8                                 | 1.4                               | 1.8                               | 25.9           | 11.2           | 0.0761         | 0.72           |
| 1.1721             | 0.9375  | -0.34                   | 0.03                                    | 1.67                                 | 1.69                                 | 0.13                                      | 2.91                                 | 2.64                                 | 0.05                              | 0.04                              |                |                |                | 1.59           |

### CARACTERÍSTICAS DEL PRODUCTO

|                   |               |
|-------------------|---------------|
| Marca             | TIMKEN        |
| N° Ean13          | 3663952310961 |
| Diámetro interior | 33.34 mm      |
| Diámetro exterior | 79.38 mm      |
| Espesor           | 29.37 mm      |
| Envasado          | 1             |

[contacto@123rodamiento.mx](mailto:contacto@123rodamiento.mx)

+34 911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE